

SUBDIVISION OF T. 24 N., R. 67 E.

| Chains | |
|--------|--|
| 21.00 | Road, bears E. and W. |
| 21.70 | 'Middle Creek', 1 lk wide; 1 in. deep, course W.; wash 15 lks. wide, 3 ft. deep. |
| 24.20 | Left fork of 'Middle Creek', wash, 15 lks. wide, 3 ft. deep, course SW. There is no water in bottom of wash at this time of the year. Water get down this far, only during the spring of the years. Asc. 160 ft. over SE. slope. |
| 24.70 | Road, bears NE. and SW. |
| 36.54 | Small spring raises, and flows for about 1 ch., N.45°E. approximately 15 ch. |
| 40.00 | On SE. slope Set an iron post, 3 ft. long, 1 in. in diam., 6 ins. in the ground, to solid rock, and in a large mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked. |
| | $\begin{array}{c} \frac{1}{4} \\ \text{S } 6 \text{ S } 5 \\ 1926 \end{array}$ |
| | I deposit a limestone, 15x12x12 ins., marked with a cross, X, at base of monument. |
| | Continue asc. 20 ft. over SE. slope. |
| 46.00 | Slope changes to E. slope; asc. 30 ft. |
| 51.60 | Slope changes to S. slope; asc. 300 ft.; saddle in ridge is approximately 5 chs. to W. |
| 78.00 | Spur ridge, projects S. 20° W. from NE.; continue along W. slope to |
| 79.43 | Intersect N. bdy. of the township, 1.16 chs. W. of the cor. of secs. 31 and 32, T. 25 N., R. 67 E.; heretofore described. At point of intersection |
| | On W. slope Set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground, to solid rock, and in a large mound of stone, for the closing cor. of secs. 5 and 6, with brass cap marked |