


SUBDIVISION OF T. 20 $\frac{1}{2}$  N., R. 69 E.

Chains

- 45.00 Lower end of a reservoir, capacity, about 75,000 gals. bears East, approximately 15 chs to center of dam.
- 45.70 Road, bears NE. to Mike Springs, and SW. to Aurum, Nev.
- 50.00 Small log cabin, 10x12 ft, bears East, approximately 16 chs. dist., and Mike Springs about 1 ch. E of cabin. This spring is well developed and covered, with a 6 ins. pipe leading out from main spring.
- 59.89 Intersect the Fourth Standard Parallel North, thru Range 69 East, at a point, 5.21 chs. E. of the standard corner of secs. 31 and 32, T. 21 N R 69 E., which is an iron post, 3 ins. in diam., extending 12 ins. above the ground, properly marked and witnessed as described in the official record of the Fourth Standard Parallel North, thru Range 69 E.

At point of intersection on the low rolling divide between Snake Valley and Spring Valley, bears NE. and SW.

Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the closing cor. of secs. 33 and 34, with brass cap marked



1926

Deposit a limestone, 3x3x3 ins., marked with a cross, X, at the base of the monument.

No other accessories available and pits impracticable.

Land, rolling; general drainage SW.

Soil, sandy and gravelly clay loam; 3rd rate.

Timber, pinon pine and juniper.

Undergrowth, sagebrush, shadscale, white sage and native grasses.

Good grazing.