

Establishment of Quarter-Section Corners on
West Boundary of T. 25 N., R. 65 E.

Chains

80.02 The closing cor. of secs. 6 and 7, hereinafter described.

North, on W. bdy. sec. 6.

2.51 The original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is a cedar post, 3 ins. square, extending 14 ins. above ground, firmly set, properly marked and witnessed as described in official returns of T. 25 N., R. 64 E. I deface the marks on post pertaining to sec. 6. This cor. now refers only to sec. 1, T. 25 N., R. 64 E.

40.00 Northing of 40.00 chs. from closing cor. of secs. 6 and 7; set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. on W. bdy. sec. 6, T. 25 N., R. 65 E., with brass cap marked

| $\frac{1}{4}$
S6

1927

Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

63.53 The original closing cor. of T. 25 N., Rs. 64 and 65 E., which is limestone, 6x9x5 ins. above ground, firmly set, properly marked and witnessed as described in official records of T. 25 N., R. 64 E.

SUBDIVISION OF T. 25 N., R. 65 E.

From the original cor. of secs. 1, 2, 35 and 36 on S. bdy. of tp., which is an iron post, 2 ins. dia., extending 14 ins. above ground, firmly set, properly marked and witnessed as described in official records of T. 24 N., R. 65 E. A cedar post, 5 ins. dia., 6 ft. high is set alongside of cor. This cor. is situated near bottom of small swale, draining NE. A spring of good water, bears N. 59° E., 6.65 chs. dist.

Thence,

N. 0°01' W., bet. secs. 35 and 36.

Over high, rolling mountainous land, through medium