Chains	
80.00	On a gentle N. slope, 100 ft. below spur at 60 chs., Set an iron post, 3 ft. long, 2 ins. dia. 6 ins. in the ground to bedrock, and supported by a large mound of stone, 5 ft. base, 2 ft. high, for cor. of secs. 1, 2, 11 and 12, with brass cap marked

T25N	R65E
S2	S1
S11	S12

1927

Deposit a quart of glass at base of post. No other accessories available.

The head of "BECKY SPRING", a small spring of good water, flows N., bears S.25° W., 23.25 chs. dist.

S. ½ mile is rolling mountainous: N. ½ mile is rolling land: general exposure and drainage northerly on mile.

Soil, shallow sandy and gravelly loam, mixed with rock; 3rd rate.

Timber, very scattered scrub cedar and pinon on S. ½ mile.

Undergrowth, medium sagebrush, shadscale and few greasewoods.

N. 89°52' E., on random line bet. secs. 1 and 12.

40.00 Set temp. ¼ sec. cor.

79.96 Intersect E. bdy. of tp., 12 lks. S. of the cor. of secs. 1, 6, 7 and 12, which is an iron post, 2 ins. dia., extending 12 ins. above ground, firmly set, properly marked and witnessed as described in survey of T. 25 N., R. 66 E.

Thence

S. 89°47' W., on true line bet. secs. 1 and 12.

Over gently rolling land facing nearly N., through short undergrowth.

5.10 Wash, 10 lks. wide, 2 ft. deep, in ravine, 10 ft. deep, drains N.10°W.; a few scattered cedars along this ravine.