

Subdivision of T. 25 N., R. 65 E.

Chains

6.30 Dim road, bears N.85°E. and S.85° W.

39.98 On a gentle N. exposure,

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \begin{array}{c} S1 \\ \hline S12 \\ 1927 \end{array}$$

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

75.00 Dim, old road, bears N.30°E. and S.30°W.

79.96 The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling with a gradual northerly exposure and drainage.

Soil, gravelly clay and stony; 2nd to 3rd rates.

Undergrowth, medium sagebrush and shadscale.

No timber.

N. 0°01' W., on true line bet. secs. 1 and 2.

Over gently rolling land facing N., through short undergrowth; gently descending.

35.90 Road, bears N.45°E. and S.45°W.

40.00 On gentle N. slope, 100 ft. below sec. cor.,

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\frac{1}{4} \begin{array}{c} S 2 \quad | \quad S 1 \\ \hline 1927 \end{array}$$

Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.

And deposit a quart of glass at base of post.

47.60 Road, bears N.75°E. and S.75°W.

54.60 Intersect the 5th standard parallel N., at N. 89°00' W.,

21.34 chs. dist. from the standard cor. of T. 26 N.,

Rs. 65 and 66 E., heretofore described on page 5.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. dia., 26 ins. in the ground, for closing cor. of secs. 1 and 2, with