Subdivision of the SE. ¼ of sec. 5, T. 33 N., R. 36 E.

| Chains. | |
|---|---|
| 20.00 | At the proportionate point, S. 89° 57' W. from the cor. of secs. 4, 5, 8 and 9, set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the east 1/16 cor. of secs. 5 and 8, with brass cap mkd.<br>E 1/16 S5/S8<br>1925<br>from which<br>A juniper, 8 ins. in diam., bears N. 9¾° W., 57 lks. dist., marked E 1/16 S 5 BT<br>A juniper, 6 ins. in diam., bears S. 52¾° W., 36 lks. dist., marked E 1/16 S 8 BT |
| | From the ¼ sec. cor. of secs. 5 and 6, |
| | East, on a blank line. |
| 40.00 | Set temp. point for the center ¼ cor. of sec. 5. |
| 79.86 | Intersect the ¼ sec. cor. of secs. 4 and 5. |
| | By a trial line for azimuth only the true bearing of the center line bet. the ¼ sec. cor. of secs. 5 and 8 and the ¼ sec. cor. of secs. 5 and 32 is N. 0° 39' W. |
| | From the ¼ sec. cor. of secs. 5 and 8, |
| | N. 0° 39' W., on the center line. |
| 20.00 | Set temp. point for the center south 1/16 cor. |
| 40.20 | Intersect the temp. point previously set on the East and West center line. At point of intersection, set an iron post, 3 ft. long, 1 in. in diam., 22 ins. in the ground, to solid rock, in a mound of stone, 2 ft. base, 12 ins. high, for the center ¼ sec. cor., with brass cap mkd.<br>C ¼ S 5<br>1925<br>from which<br>A juniper, 4 ins. in diam., bears S. 61¼° E., 143.8 lks. dist., marked C¼ S5 BT<br>A juniper, 5 ins. in diam., bears N. 56° W., 104 lks. dist., marked C¼ S5 B T |