

RESURVEY OF  
FRACTIONAL LINE BET. SECS. 14 AND 15, T. 24 N., R. 21 E.

Chains

T24N | R21E  
S 15 | S 14  
    /  \  
    MC

1925

Deposit broken glass at base of post, and raise a small mound of stone around post.

Thence over rolling land, through a medium undergrowth.

15.10 Old road, brs. N.10°E., and S. 10°W.

20.90 Road, brs. NE. and SW.

29.25 Wire fence, brs. E. and W.

39.00 Recross road, brs. N. 5°W., and S. 5°E.

40.00 Proportionate distance

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S 15 | S 14  
1925

Deposit broken glass at base of post.

50.50 The meander cor. of frac. secs. 14 and 15.

Land, rolling.

Soil, gravelly loam; 3rd rate.

Undergrowth, sagebrush.

No timber. Good grazing.

RETRACEMENT OF

MEANDERS THROUGH SEC. 15, T. 24 N., R. 21 E.

From meander cor. of frac. secs. 14 and 15, thence with meanders through sec. 15.

N. 32° 45'W., 8.25 chs. to angle point; thence

N. 41° 00'W., 6.70 chs. to angle point; thence

N. 7° 45'W., 3.70 chs. to angle point; thence

N. 71° 15'W., 5.65 chs. to angle point; thence

N. 62° 15'W., 8.90 chs. to angle point, thence

N. 19° 30'W., 8.16 chs. to M.C. bet., secs. 10 and 15.