

RETRACEMENT OF PORTION OF WEST BOUNDARY
T. 19 N., R. 54 E.

Chains	<p>From the original cor. of secs. 1, 6, 7, and 12, Tps. 19 N., Rs. 53 and 54 E., which is a stone, 16x14x12 ins., above ground, firmly set, marked and witnessed as described in the official record.</p> <p>North, along W. bdy. sec. 6.</p> <p>Over mountainous bench land, through scattering scrub timber and dense undergrowth.</p> <p>Desc. general NE. slope 80 ft. to 34.55 chs.</p>
30.73	<p>Fall 14 lks. W. of the cor. of Tps. 19 and 20 N., R. 53 E., hereinafter described</p> <p>Thence on same line with continuous measurement</p>
34.55	<p>Draw, drains N. 45° W. about 15 chs., thence N.</p> <p>Asc. rocky SW. slope 40 ft. to 43.45 chs.</p>
40.23	<p>Fall 19 lks. W. of the original $\frac{1}{4}$ sec. cor. of sec. 6, which is a stone, 16x14x10 ins. above ground, firmly set, marked and witnessed as described in the official record</p> <p>The bearing of this half mile therefore is N. 0° 16' E., and the dist. 40.23 chs.</p> <p>Thence on same line with continuous measurement</p>
43.45	<p>Desc. general N. slope 10 ft. to</p>
50.35	<p>Fall 23.4 lks. W. of the original cor. of Tps. 19 and 20 N., R. 54 E., which is a stone, 18x12x5 ins. above ground, firmly set, marked and witnessed as described in the official record.</p> <p>The bearing of this fractional mile therefore is N. 0° 16' E., and the dist. 50.35 chs.</p>

DEPENDENT RESURVEY OF EAST BOUNDARY OF T. 20 N., R. 53 E.

REESTABLISHMENT OF THE SURVEYS EXECUTED BY C. C.
TRACY, U. S. DEPUTY SURVEYOR IN 1868.

Random lines.

	<p>From the cor. of Tps. 19 and 20 N., R. 54 E.</p> <p>North, along W. bdy. sec. 31.</p>
40.00	<p>Find no trace of original $\frac{1}{4}$ sec. cor.</p>
30.47	<p>Fall 1.03 chs. E. of the original cor. of secs. 25, 30, 31, and 36, hereinafter described.</p> <p>The bearing of this mile therefore is N. 0° 44' W. and the dist. 30.48 chs.</p> <p>From sec. cor.</p> <p>North, along W. bdy. sec. 30.</p>
40.00	<p>Find no trace of original $\frac{1}{4}$ sec. cor.</p>