

INDEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS OF
T. 20 N., R. 53 E.

- Chains Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
- 34 | 33
1933
- 18x18x12 ins., N. and S. of post, 3 ft. dist. dig pits,
- 71.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E. about 4 chs., thence N. 10° E.
- 50.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the cor. of lots 11 and 12 of sec. 3, and lots 9 and 16 of sec. 4, with brass cap mkd.
- 9 | 11
16 | 12
34 | 33
1933
- 95.77 Intersect 4th stan. parallel north, which was resurveyed as the S. bdy. of T. 21 N., R. 53 E. in conjunction with the survey of this Tp., N. 88° 07' E., 9.26 chs. from the stan. cor. of secs. 33 and 34, which is described in Book "B" of field notes under Group No. 133 at point of intersection.
- Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the closing cor. of secs. 3 and 4, with brass cap mkd.
- T21NR53E
S 34
34 | 33
T20NR53E
30
1933
- 18x18x12 ins., E., S., and W. of post, 3 ft. dist. dig pits,
- Land, gently rolling. Soil, sandy clay loam, 2nd rate. Timber, none. Undergrowth, sagebrush, scattering grass. General drainage, NE. Grazing, fair.

DEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS OF
T. 20 N., R. 53 E.

REESTABLISHMENT OF THE SURVEYS EXECUTED BY E. L. BRIDGES
AND J. W. EATON, U. S. DEPUTY SURVEYORS IN 1879.

Random lines.

From the cor. of secs. 32 and 33, on S. bdy. of T.
North, bet. secs. 32 and 33.

40.41 Fall 7 lks. E. of the original $\frac{1}{4}$ sec. cor., hereinafter described.

The bearing of this half mile therefore is N. 0° 06' W., and the dist. 40.41 chs.

From $\frac{1}{4}$ sec. cor.

North, with new measurement.

40.39 Fall 7 lks. E. of the original cor. of secs. 28, 29, 32, and 33, hereinafter described.