DEPENDENT RESURVEY OF NORTH BOUNDARY T. 21 N. R. 53 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 5, with brass cap mkd.

‡ S5 1933

dig pits

18x18x12 ins., E. and W. of post, 3 ft. dist.

80.04

Proportionate point for sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the cor. of secs. 5 and 6, with brass cap mkd.

\$6 \$5 T21NR53E 1933

Pits impracticable; no stone available for mound.

Land, gently rolling.
Soil, 27 ins. sand and clay loam, 2nd and 3rd rate.
Timber, none.
Undergrowth, sagebrush.
General drainage, NW.
Grazing, poor.

S. 88°07' W., along N. bdy. sec. 6.

6.30 Old unused road, bears N. 10° W. and S. 15° E.

40.02

Proportionate point for \(\frac{1}{4} \) sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap mkd.

1 s6 1933

Pits impracticable; no stone available for mound.

78.16

The cor. of Tps. 21 N., Rs. 52 and 53 E.

Land, gently rolling.
Soil, sand and clay loam with some small sand dunes, 2nd rate.
Timber, none.

Undergrowth, sagebrush, rye grass. General drainage, NW.

General drainage, NW. Grazing, fair.

SECTIONAL CORRECTION LINE.

From the cor. of secs. 25 and 36, on E. bdy. of Tp., hereinbefore described.

West, on a random line, making proper offsets to the north from the tangent to the parallel at intervals of 40.00chs., setting temp. \(\frac{1}{4}\) sec. and sec. cors. along the line bet. secs. 25 and 36, 26 and 35, 27 and 34, 28 and 33, 29 and 32, and 30 and 31. At 480.69 chs. the parallel intersects W. bdy. of Tp., N. 0°31' E., 11.49 chs. from the cor. of secs. 25 and 36.