

552

## SURVEY OF PORTION OF SUBDIVISIONS T. 21 N., R. 53 E.

Chains	From the temp. point for the cor. of secs. 25, 26, 35, and 36, on sectional correction line.
	S. 0°11' W., on a random line, bet. secs. 35 and 36, parallel to the mean course of the east boundary of the township.
40.00	Set temp. $\frac{1}{4}$ Sec. cor.
82.63	Intersect the standard cor. of secs. 35 and 36, on S. bdy. of Tp.
	Thence
	N. 0°11' E., on true line bet. secs. 35 and 36.
	Over gently rolling land, through dense undergrowth.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\   \\ S36 \end{array}$
	1933
	18x18x12 ins. N. and S. of post, 3 ft. dist. dig pits,
42.63	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the $\frac{1}{4}$ sec. cor. of sec. 35, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\   \\ S35 \end{array}$
	1933
	18x18x12 ins., N. and S. of post, 3 ft. dist. dig pits,
82.63	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a glass bottle deposited at the base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	T21NR53E
	$\begin{array}{c c} S26 & S25 \\ \hline S35 & S36 \end{array}$
	1933
	18x18x12 ins., one in each section, 3 ft. dist. dig pits,
	Land, gentle rolling.
	Soil, S. half sandy clay loam, 2nd rate; N. half 14 ins. clay loam over hardpan. 3rd rate.
	Timber, none.
	Undergrowth, sagebrush, white sage.
	General drainage, NW.
	Grazing, poor.
	From the cor. of secs. 25 and 36, on E. bdy. of Tp.
	West, on sectional correction line.
	Over gentle rolling land, through dense undergrowth.