

562

SURVEY OF PORTION OF SUBDIVISIONS T. 21 N., R. 53 E.

Chains East, on a random line bet. secs. 11 and 14.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 79.94 Fall 7 lks. N. of the cor. of secs. 11, 12, 13, and 14.
 Thence
 N. $89^{\circ} 57'$ W., on true line bet. secs. 11 and 14.
 Over gently rolling land, through dense undergrowth.
 39.45 Improved road, bears N. 65° E. and S. 65° W.
 39.97 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, with a glass bottle deposited at the base,
 for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 11
 $\frac{1}{4}$ S 14
 1933

18x18x12 ins., E. and W. of post, 3 ft. dist. dig pits,

79.94 The cor. of secs. 10, 11, 14, and 15.
 Land, gently rolling.
 Soil, 27 ins. sandy clay loam, 2nd rate.
 Timber, none.
 Undergrowth, sagebrush.
 General drainage, NW.
 Grazing, poor.

INDEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS
 T. 21 N., R. 53 E.

SUPERSEDING THE SURVEYS EXECUTED BY E. L. BRIDGES
 AND J. W. EATON, U. S. DEPUTY SURVEYORS IN 1879

From the cor. of secs. 10, 11, 14, and 15.

N. $0^{\circ} 11'$ E., bet. secs. 10 and 11.

Over gently rolling land, through dense undergrowth.

40.00 Find no trace of original $\frac{1}{4}$ sec. cor.
 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in
 the ground, with a glass bottle deposited at the base,
 for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S10 | S11
 1933

Pits impracticable; no stone available.

80.00 Find no trace of original sec. cor.
 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
 the ground, with a glass bottle deposited at the base,
 for the cor. of secs. 2, 3, 10, and 11, with brass cap
 mkd.

T21NR53E
 S3 | S2
 S10 | S11
 1933