

Retracement of a portion of the Ninth Standard Parallel North in R.23E.

Chains From the closing cor. of T. 45 N., Rs. 23 and 24 E.,  
hereinafter described.

East on retracement, along the Ninth Standard Parallel  
North.

8.69 Fall 10 lks. S. of the standard cor. of T. 46 N., R. 23  
E., hereinafter described. The course of this line is  
N. 89° 20' E. and the distance is 8.69 chs.

-----  
Dependent Resurvey of the S. Bdy. of T. 45 N., R. 24 E.  
~~Reestablishment of surveys executed by G.W. Garside, U.S.~~  
Deputy Surveyor in 1877  
-----

Alongside the original corner of Ts. 44 and 45 N., Rs. 23  
and 24 E., which is a granite stone, 14x12x8 ins. marked  
with 6 grooves on N., S., E. and W. faces, firmly set in  
a mound of stone, set an iron post, 5 ft. long, 3 ins. in  
diam., 28 ins. in the ground, for the cor. of Ts. 44 and  
45 N., Rs. 23 and 24 E., with brass cap mkd.

T45N  
R23E | R24E  
-----  
S36 | S31  
-----  
S1 | S6  
T44N  
1927

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of the cor.

Thence

S. 89° 23' E., on a true line, bet. secs. 6 and 31 on the  
S. Bdy. of the township.

Asc. gradual NW. slope over slightly rolling land.

33.00 Top of low flat spur, projects N. Desc. gradual NE. slope.

37.95 (Record) Set an iron post, 3 ft. long, 1 in. in diam.,

28 ins. in the ground, for the ¼ sec. cor., sec. 31, T.  
45 N., R. 24 E. with brass cap mkd.

¼ S31  
-----  
1927

38.59 Raise a mound of stone 2 ft. base, 1½ ft. high, N. of cor.  
Proportionate point. Set an iron post, 3 ft. long, 1 in.  
in diam., 26 ins. in the ground for ¼ sec. cor. Sec. 6,  
T. 44 N., R. 24 E., with brass cap mkd.

¼ S6  
-----  
1929

Raise a mound of stone 3 ft. base, 2 ft. high S. of cor.