

Dependent Resurvey of the W. Bdy. of T. 45 N., R. 24 E.

Chains

Reestablishment of Surveys executed by Benson and Putnam, U.S. Deputy Surveyors in 1881.

From the cor. of Ts. 44 and 45 N., Rs. 23 and 24 E., hereinbefore described

N. $0^{\circ} 08'$ E. on a true line, on the E. Bdy. of sec. 36.

Desc. gradual NW. slope over slightly rolling land.

34.77 True point for the $\frac{1}{4}$ sec. cor. of sec. 31, hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 31, only, with brass cap mkd.

$\frac{1}{4}$
S31
1927

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of corner

40.35 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is a granite stone, 8 x 8 x 6 ins., marked $\frac{1}{4}$ on N. face, set in a mound of stone. Alongside, set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd.

$\frac{1}{4}$
S36
1927

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor. From the $\frac{1}{4}$ sec. cor. N. $0^{\circ} 19'$ E.

Desc. gradual NE. slope.

61.60 Shallow wash, drains NW.

69.50 Shallow wash, drains NW.

74.77 True point for the cor. of secs. 30 and 31, hereinafter determined. Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 30 and 31, with brass cap mkd.