

Dependent Resurvey of the W. Bdy. of T. 45 N., R. 24 E.

- Chains. N. $0^{\circ} 21'$ E. on a true line, bet. secs. 1 and 6.
- .20 Top of ridge, bears E. and W.
Desc. N. slope 70 ft. over rolling land.
- 12.65 Dry wash, drains S. 85° E. Asc. S. slope 25 Ft.
- 21.60 Top of low spur, projects E.
- 32.52 A northing of 40.00 chs. from the cor. of secs. 6 and 7.
On crest of low spur projecting E. set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 6, only, with brass cap mkd.
- $\frac{1}{4}$
 S6
 1927
- Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of the cor.
- 34.50 Desc. N. slope 70 ft.
- 39.74 Intersect the original $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is an old mound of stone with no evidence of markings. In center of mound of stone, in shallow wash draining S. 85° E. set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd.
- $\frac{1}{4}$
 S1
 1927
- Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.
- From the $\frac{1}{4}$ sec. cor. N. $0^{\circ} 28'$ E. on a true line.
Asc. S. slope 130 ft. over rolling land.
- 70.60 Top of ridge, bears S. 75° E. and N. 75° W.
Desc. N. slope 30 ft.
- 80.04 Intersect the closing cor. of T. 45 N., Rs. 23 and 24 E., which is a granite stone, 10 x 8 x 4 ins., marked with 3 grooves on E., W. and S. faces, firmly set in a mound of stone. Alongside, set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the closing cor. of T. 45 N., Rs. 23 and 24 E., with brass cap mkd.