

Survey of the N. Bdy. of T. 45 N., R. 24 E.

Chains.

From the cor. of Ts. 45 and $45\frac{1}{2}$ N., R. 24 E.,
West on a random line, setting temporary points at
40.00 and 80.00 chs.

467.90 Intersect the standard cor. of T. 46 N., R. 23 and 24 E.,
hereinafter described.

Dependent Resurvey of a portion of the
Ninth Standard Parallel North through R. 23 E.

From the closing cor. of T. 45 N., Rs. 23 and
24 E., hereinbefore described,
N. $89^{\circ} 20'$ E., on a true line, on the N. Bdy. of sec. 6,
T. 45 N., R. 24 E.

Desc. along N. slope 30 ft. over rolling land.

8.69 Intersect the standard cor. of T. 46 N., Rs. 23 and
24 E., which is a granite stone, 26 x 14 x 4 ins.,
marked with 6 grooves on N., W. and E. faces and SC
on S. face, set in a mound of stone. Alongside, set an
iron post, 3 ft. long, 3 ins. in diam., 20 ins. in the
ground, to solid rock, in a mound of stone, for the
standard cor. of Ts. $45\frac{1}{2}$ and 46 N., Rs. 23 and 24 E.,
with brass cap mkd.

S	C
T46N	T45 $\frac{1}{2}$ N
R23E	R24E
S36	S31
S6	
T45NR24E	
1927	

Survey of a portion of the N. Bdy. of T. 45 N., R. 24 E.

From the standard cor. of Ts. $45\frac{1}{2}$ and 46 N., Rs. 23 and
24 E. with continuous measurement from the
closing cor. of T. 45 N., Rs. 23 and 24 E.

East on a true line, bet. secs. 6 and 31.

Desc. along NE. slope 100 ft. over rolling land.

36.59 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.