

Independent resurvey of the Ninth Standard Parallel North  
through a portion of R. 24 E.

Alongside the original standard corner of secs. 32 and 33, T. 46 N., R. 24 E., which is a granite stone, 10 x 6 x 5 ins. above ground, marked with 4 grooves on E. face and 2 grooves on W. face and SC on N. face, firmly set with a mound of stone north of corner, set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground, to solid rock, in a mound of stone, 5 ft. base, 30 ins. high, for the standard cor. of secs. 32 and 33, with brass cap mkd.

S C  
T46N | R24E  
S32 | S33  
1927

West on a true line, on the S. Bdy. of sec. 32.

Asc. SE. slope 70 ft. over rocky SE. slope of canyon.

- 11.69 True point for the  $\frac{1}{4}$  sec. cor. for the N. Bdy. of sec. 34, hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground, to solid rock, and 18 ins. in a mound of stone, for the  $\frac{1}{4}$  sec. cor. of sec. 34 only, with brass cap mkd.

$\frac{1}{4}$  S34  
1927

At base of post deposit a volcanic stone, 10 x 8 x 4 ins., marked with cross (x)

- 15.40 Top of spur, projects S. Desc. 30 ft. to  $\frac{1}{4}$  sec. cor.

- 39.96 Fall 2 lks. N. of the original standard  $\frac{1}{4}$  sec. cor., which is granite stone, 12 x 6 x 4 ins. above ground, marked SC  $\frac{1}{4}$  on N. face with mound of stone north of corner. I destroy all evidence of this corner.

- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 13 ins. in the ground, to solid rock, and 23 ins. in a mound of stone, for the standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S C  
 $\frac{1}{4}$  S32  
1927

At base of post deposit a granite stone, 12 x 8 x 5 ins., marked with cross (x)

Desc. 10 ft.

- 42.70 Creek with running water 2 lks. wide, 3 ins. deep, in