

Independent resurvey of the Ninth Standard Parallel North
through a portion of R. 24 E.

- Chains. bottom of Little Echo Canyon, course SE. Asc. 90 ft.
- 48.60 Recross creek draining NE. Asc. rocky SE. slope of canyon 30 ft.
- 53.80 Top of small rim, facing SE. Asc. SE. slope 60 ft.
- 68.80 Top of spur, projects SW.
- 79.96 Fall 9 lks. N. of the original standard cor. of secs. 31 and 32, which is a granite stone, 12 x 8 x 6 ins. above ground, marked with 5 grooves on E. face, 1 groove on W. face and SC on N. face, with mound of stone N. of cor. I destroy all evidence of this corner.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the standard cor. of secs. 31 and 32, with brass cap mkd.

| | |
|------|------|
| S | C |
| T46N | R24E |
| S31 | S32 |
| 1927 | |

Raise a mound of stone 2 ft. base, 1½ ft. high, N. of the cor.

Land: rolling.

Soil: rocky and gravelly clay.

Undergrowth: sage. Fair growth of grass.

West on the S. Bdy. of sec. 31.

Desc. SW. slope 25 ft. over rolling land to dry wash.

- 11.80 True point for the ¼ sec. cor. on the N. Bdy. of sec. 33, hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor. of sec. 33 only, with brass cap mkd.

| | |
|------|-----|
| ¼ | S33 |
| 1927 | |

Raise a mound of stone 2 ft. base, 1½ ft. high, S. of the cor.

- 12.70 Shallow dry wash, drains S. Asc. gradual E. slope 55 ft.

- 39.95 Fall 16 lks. N. of the original ¼ sec. cor., which is a granite stone, 14 x 10 x 6 ins., above ground, marked SC ¼ on N. face with mound of stone N. I destroy all evidence of this corner.