

Independent resurvey of the Ninth Standard Parallel North  
through fractional Range 23½ East.

Chains.	West on a true line, on the S. Bdy. of sec. 35. Desc. gradual SW. slope 15 ft. over rolling land.
11.87	True point for the ¼ sec. cor. on the N. Bdy. of sec. 31, hereinafter determined. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor. of sec. 31 only, with brass cap mkd. <div style="text-align: center;">S 31 ¼ 1927</div>
	Raise a mound of stone 2 ft. base, 1½ ft. high, S. of the cor. Desc. SW. slope 80 ft.
30.90	Dry wash, drains S. 20° E. Asc. SE. slope 55 ft.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the standard ¼ sec. cor., with brass cap mkd. <div style="text-align: center;">S C ¼ S 35 1927</div>
	At base of post deposit a granite stone 8 x 8 x 4 ins. marked with cross (x) No other accessories available.
40.19	Intersect the E. Bdy. of T. 46 N., R. 23 E., at a point 49 lks. N. of the standard closing corner of T. 46 N., R. 24 E., which is a basalt stone, 16 x 8 x 6 ins. above ground, marked with 6 grooves on N. and S. faces and with CC on E. face, which corner I destroy, and, S. 0° 21' E., 5.68 chs. distant from the corner of sections 25 and 36 on the E. Bdy. of T. 46 N., R. 23 E., hereinbefore described. At the point of intersection set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the standard closing cor. of T. 46 N., R. 23½ E., with brass cap mkd. <div style="text-align: center;">S C T 46 N R 23½ E S 35 CC 1927</div>
	Raise a mound of stone, 3 ft. base, 2½ ft. high, E. of the cor. Land: rolling. Soil: rocky and gravelly clay. Undergrowth: sage. Fair growth of grass.