

INDEPENDENT RESURVEY OF
SIXTH STANDARD PARALLEL NORTH, THROUGH RANGE 38 EAST

Chains
58.10 Spur, projects N. 15° E.
Desc. NW. slope 30 ft. to
62.00 Ravine, drains N., heads about 8 chs. SW.
Asc. NE. slope 95 ft. to
70.70 Rocky spur, projects N.
Desc. rocky NW. slope 125 ft. to
77.10 Main ravine, drains N. 80° E.
Asc. rocky SE. slope 160 ft. to
80.00 On rock out cropping
Set an iron post, 3 ft. long, 2 ins. dia., over chiseled
(X) cross, in a mound of stone, for the standard cor.
of secs. 31 and 32, with brass cap mkd

SC
T31N R38E
S31 | S32

1928

No suitable trees available within limits

Find no trace of old standard sec. cor.

Land, rough mountainous. Soil, rocky, 3rd and 4th rate.

Timber, scattering juniper. Undergrowth, sage.

General drainage, NE. Grazing, fair.

West, on independent resurvey, on S. boundary of sec. 31
Over rough mountainous land through scattering timber
Asc. steep rocky SE. slope 445 ft. to 28.90
6.04 Point for closing cor. of secs. 5 and 6
28.90 Asc. rocky broken E. slope 185 ft. to 53.00
40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
ground to solid rock, in a mound of stone, for the
standard $\frac{1}{4}$ sec. cor., with brass cap mkd

SC
 $\frac{1}{4}$ S 31

1928

At base of post deposit a mkd(X) quartzite stone, 6x6x6 ins.