

Dependent resurvey of a portion of east boundary of T. 30 N., R. 38 E.

- Chains. N. 0° 26' W., on dependent resurvey between secs. 1 and 6
 Over mountainous land
 Asc. S. slope 60 ft. to
 5.90 Spur, projects E.
 Thence along broken E. slope
 16.90 Draw, drains E., heads about 3 chs. W.
 Asc. SE. slope 15 ft. to
 22.30 Desc. NE. slope
 33.25 Wash in draw, 20 lks. wide, 3 ft. deep, drains S. 45° E.
 Asc. SW. slope 340 ft. to 61.35
 38.67 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the
 ground to solid rock, in a mound of stone, for the $\frac{1}{4}$
 sec. cor. of sec. 1 only, with brass cap mkd
 $\frac{1}{4}$
 S1
 1928
 At base of post deposit a mkd(X) trap stone, 6x4x2 ins.
 39.88 The old $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is a wooden
 post, lying on top of mound of earth, marked $\frac{1}{4}$ S1 on
 one face, and $\frac{1}{4}$ S6 on other face
 In center of mound, alongside old post
 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
 ground to solid rock, in a mound of stone, for the $\frac{1}{4}$
 sec. cor. of sec. 6 only, with brass cap mkd
 $\frac{1}{4}$
 S6
 1928
 At base of post deposit a mkd(X) scoria stone, 6x6x4 ins.
 Thence
 N. 0° 21' W., on dependent resurvey, continuing measure-
 ment
 61.35 Rocky spur, projects S. 75° E.
 Desc. steep rocky NE. slope 185 ft. to
 78.40 Ravine, drains S. 80° E.