

SUBDIVISIONS T. 30 N., R. 38 E.

Chains

43.50 Draw, drains W., heads about 8 chs. E.

Asc. SW. slope 200 ft. to

58.05 Spur, projects N. 70° W.

Desc. NW. slope 215 ft. to

67.30 Desc. NE. slope 125 ft. to

80.88 Intersect the Sixth Standard Parallel 6.48 chs. W. of the standard cor. of secs. 35 and 36, and at point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 1 and 2, with brass cap mkd

T31NR38E
S 35
S2 S1
T30N R38E
CC
1928

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor. Land, mountainous. Soil, sandy clay loam, 3rd rate. Timber, none. Undergrowth, sage, shadscale. General drainage, SE. and NW. Grazing, poor.

From the cor. of secs. 22 and 23
N. 0° 01' W., between secs. 22 and 23
Over mountainous land

Desc. N. slope 40 ft. to

6.25 Draw, drains E. from NW.

Asc. SW. slope 170 ft. to

31.40 Spur, projects S. 85° E.

Desc. NE. slope 175 ft. to draw

38.91 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground to solid rock, in a mound of stone, for the ¼ sec. cor., with brass cap mkd

¼
S22 S23
1928

At base of post deposit a mkd(X) lava stone, 6x4x3 ins.