

SUBDIVISIONS T. 30 N., R. 38 E.

Chains Land, mountainous. Soil, gravelly and rocky, 4th rate.
 Timber, none. Undergrowth, sage.
 General drainage, NW. Grazing, poor.

N. 0° 01' W., between secs. 2 and 3
 Over mountainous land
 Asc. S. slope 110 ft. to

14.85 Spur, projects N. 20° W.

16.45 Desc. NE. slope 195 ft. to

35.50 Draw, drains W.
 Asc. SE. slope 90 ft. to spur

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
 ground to solid rock, in a mound of stone, for the $\frac{1}{4}$
 sec. cor., with brass cap mkd
 $\frac{1}{4}$
 S3 | S2
 1928

At base of post deposit a mkd(X) granite stone, 8x6x2 ins.

48.40 Spur, projects W.
 Desc. NW. slope 100 ft. to

56.50 Head of draw, drains N. 75° W.
 Asc. SW. slope 35 ft. to

64.65 Spur, projects N. 80° W.
 Desc. NW. slope 70 ft. to

73.65 Asc. SW. slope 50 ft. to

80.77 Intersect the Sixth Standard Parallel North, 6.38 chs.
 West of the standard cor. of secs. 34 and 35, and at
 point of intersection
 Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in
 the ground to solid rock, in a mound of stone, for the
 closing cor. of secs. 2 and 3; with brass cap mkd
 T31NR38E
 S 34
 S3 | S2
 T30NR38E
 80
 1928

At base of post deposit a mkd(X) granite stone, 6x4x2 ins.