

## SUBDIVISIONS T. 30 N., R. 38 E.

Chains

- 61.35 Main ravine, drains E.  
Asc. SW. slope 160 ft. to spur
- 62.75 Old road, bears E. and W.
- 72.50 Spur, projects S.  $45^\circ$  E.  
Desc. NE. slope 55 ft. to
- 80.71 Intersect Sixth Standard Parallel North, 6.40 chs. W. of  
the standard cor. of secs. 33 and 34, and at point of  
intersection  
Set an iron post, 3 ft. long, 2 ins. dia., on solid rock  
outcropping, over a chiseled(-X) cross, in a mound of  
stone, for the closing cor. of secs. 3 and 4, with  
brass cap mkd

T31NR38E

S 33

S4 S3

T30NR38E

CC

1928

Land, mountainous. Soil, rocky, 4th rate.

Timber, scrubby juniper. Undergrowth, sage, willows.

General drainage, E. Grazing, fair.

From the cor. of secs. 8 and 9

N.  $0^\circ 02'$  W., between secs. 8 and 9

Over mountainous land through scattering timber

Asc. SE. slope 40 ft. to 12.70

3.70 Old road, bears N.  $35^\circ$  W. and S.  $35^\circ$  E.

12.70 Desc. NE. slope 45 ft. to

21.25 Desc. NW. slope 165 ft. to

37.05 Ravine, drains N.  $70^\circ$  E.

Asc. SE. slope 195 ft. to 60.05

39.14 Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the  
ground to solid rock, in a mound of stone, for the  $\frac{1}{4}$   
sec. cor. of sec. 9 only, with brass cap mkd $\frac{1}{4}$ 

S9

1928