

196

Retracement of the Fourth Standard Parallel North  
through range 34 E.

Chains. From the standard cor. of secs. 32 and 33,  
West, on retracement, on the S. Bdy. of sec. 32.  
40.00 No trace of the standard  $\frac{1}{4}$  sec. cor.  
79.92 Fall 23 lks. N. of the standard cor. of secs. 31 and 32,  
hereinafter described.  
The course of this mile is S.  $89^{\circ} 50'$  W. and the distance  
is 79.92 chs.

From the standard cor. of secs. 31 and 32,  
West, on retracement on the S. Bdy. of sec. 31.  
40.04 Fall 48 lks. N. of the standard  $\frac{1}{4}$  sec. cor., hereinafter  
described.  
The course of this  $\frac{1}{2}$  mile is S.  $89^{\circ} 19'$  W. and the  
distance is 40.04 chs.

79.33 Fall 40 lks. N. of the standard cor. of T. 21 N., Rs. 33  
and 34 E., hereinafter described.  
The course of the west  $\frac{1}{2}$  mile is N.  $89^{\circ} 53'$  W. and the  
distance is 39.29 chs.

Independent resurvey of the Fourth Standard Parallel North  
through range 34 E.

(Survey originally executed by deputy W. Epler in  
1865 under contract No. 1.)

Alongside the original standard corner of T. 21 N., Rs.  
34 and 35 E., which is a hewn post firmly set in a  
mound of earth, 4 ins. square and 30 ins. above ground,  
marked with 6 grooves on N. face, T xxl N R XXXV E on  
E. face, and TXXlNRXXXIVE SXXXVl on W. face, set an  
iron post, 3 ft. long, 3 ins. in diam., 28 ins. in the  
ground, for the standard cor. of T. 21 N., Rs. 34 and  
35 E., with brass cap mkd.

S C  
T21N  
R34E R35E

1928

At base of post deposit a trap stone 10 x 5 x 3 ins.  
marked with cross (x)

Contract J. (Epler)