

202

Independent Resurvey of the Fourth Standard Parallel North
through R. 34 E.

Chains. 41.31	<p>Fall 7 lks. N. of the original standard $\frac{1}{4}$ sec. cor., which is a granite float, 12 x 10 x 5 ins., marked $\frac{1}{4}$. I destroy all evidence of this corner. Asc. 150 ft.</p>
47.00	Slope changes to SE. Desc. 70 ft.
59.80	Dry wash, drains SE. Asc. 250 ft.
67.40	Top of short spur, projects SE. Desc. SW. slope 50 ft.
71.80	Dry wash, drains SE. Asc. NE. slope 260 ft.
80.00	Top of spur, projects SE.
80.60	<p>Intersect the standard cor. of T. 21 N., Rs. 33 and 34 E., which is a granite stone 20 x 14 x 6 ins. above ground, set in a mound of stone, marked with 6 grooves on the E. and W. faces. Alongside, set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the standard corner of T. 21 N., Rs. 33 and 34 E., with brass cap mkd,</p> <div style="text-align: center;"> <p>S C T21N R33E R34E S36 S31 ----- 1928</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor. Land: broken and mountainous. Soil: decomposed granite, shallow on crests of spurs. Undergrowth: medium growth of sage. Fair growth of grass.</p>

Dependent Resurvey of the E. Bdy. of T. 21 N., R. 34 E.

(Reestablishment of surveys executed by Deputies Stewart
and Conkling, 1881, undercontract No. 132)

Retracements.

From the standard cor. of T. 21 N., Rs. 34 and 35 E.,
hereinbefore described,
North, on retracement, setting temporary points at 40.00
and 80.00 chs. and making diligent search for old corners.
No old corners were found until a point,