

Survey of the subdivisions of T. 21 N., R. 34 E.

Chains.	
33.30	Dry wash, drains SE.
38.90	Dim road, bears NW. and SE.
40.00	Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S5 S4 1928
	Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.
46.50	Dry wash, drains SE.
58.20	Dry wash, drains SE.
63.20	Dry wash, drains SE.
71.50	Dry wash, drains SE.
76.00	Dry wash, drains SE. Asc. 30 ft.
83.08	Intersect the N. Bdy. of the township at a point, East, 12.31 chs. distant from the cor. of secs. 32 and 33. At the point of intersection set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd.
	T22N R34E S33 S5 S4 T21N R34E C C 1928
	Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.
	Land: slightly rolling.
	Soil: a gravelly and rocky clay of medium texture.
	Undergrowth: shadscale, sage and greasewood. Very scant growth of grass.
	From the true point for the standard cor. of secs. 31 and 32, on the S. Bdy. of the township,
	N. $0^{\circ} 03'$ W. bet. secs. 31 and 32.
	Asc. abrupt SW. slope 375 ft. over broken and mountainous land.
12.80	Top of spur, projects S. 70° E. Desc. NE. slope 90 ft.