

Establishment of  $\frac{1}{4}$  sec. and sec. corners for  
T. 32 N., R. 59 E., on portion of N. bdy. of T. 31 N., R. 59 E.

## Chains

ESTABLISHMENT OF QUARTER SECTION AND SECTION  
CORNERS FOR T. 32 N., R. 59 E., ON PORTION OF NORTH  
BOUNDARY OF T. 31 N., R. 59 E., ESTABLISHED BY  
C.S. SWANHOLM, U.S. SURVEYOR, IN 1922.

From the restored cor. of secs. 2, 3, 34 and 35, on N.  
bdy. of T. 31 N., R. 59 E., which is an iron post,  
2 ins. dia., extending 10 ins. above ground, firmly  
set, properly marked, and witnessed as described in  
official records of survey of T. 31 N., R. 59 E.

Thence, West along N. bdy. of T. 31 N., R. 59 E.,  
establishing new corners at regular intervals of  
40.00 chs. for T. 32 N., R. 59 E.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor. of sec. 34, T. 32 N.,  
R. 59 E. only, with brass cap marked

$\frac{1}{4}$  S34

1927

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, N.  
of cor.

40.94 The original  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, an iron  
post, 1 in. dia., extending 12 ins. above ground,  
firmly set, properly marked and witnessed. I efface  
the marks on post pertaining to sec. 34, leaving same  
marked for sec. 3, T. 31 N., R. 59 E. only,

$\frac{1}{4}$

S3

1922

And change mound of stone to S. of post.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 26 ins. in  
the ground, for cor. of secs. 33 and 34, T. 32 N.,  
R. 59 E., only, with brass cap marked

T32N	R59E
S33	S34

S3

1927

from which

An aspen, 9 ins. diam., bears N.45°E., 31 lks.  
dist., marked T32NR59ES34BT

An aspen, 9 ins. diam., bears N.24 $\frac{1}{2}$ °W., 21 $\frac{1}{2}$  lks.  
dist., marked T32NR59E S33BT