

EAST BOUNDARY OF T. 32 N., R. 58 E.

Chains

T32N	T32N
S36	S30
R58E	S31
	R59E
	1927

from which

A limber pine, 12 ins. diam., bears N. 24° E., 255
lks. dist., marked T32N R59E S30 BT

A limber pine, 16 ins. diam., bears S. 60° E., 37
lks. dist., marked T32N R59E S31 BT

Cor. set on steep E. slope, 110 ft. below last cor.

Continue along steep E. slope, entering heavier timber.

24.30 Stream, 5 lks. wide, 4 ins. deep, very swift current,
in bottom of shallow ravine on steep E. slope, drains
N. 80° E., 125 ft. below last cor.; stream heads about
 $\frac{1}{4}$ mile W. in small lake.

Asc. steep, rocky NE. slope, 230 ft. to

37.00 Top of ascent on E. slope, bears E. and W.; continue
along steep E. slope, leaving nearly all timber, and
enter granite bedrock.

40.00 On steep E. slope, 15 ft. below top of ascent,
Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in
ground to bedrock, and supported by a large mound of
stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S36
1927

from which

Ledge outcrop, bears S. 40° W., 44 lks. dist., marked
with a 12 in. cross and BO thus

B/O

Impracticable to make additional markings on outcrop on
account of broken nature of the rock.

A small ledge facing E. and bearing N. and S., bears E.
of cor. 1 ch. dist.

56.15 True point for $\frac{1}{4}$ sec. cor. of sec. 31, T. 32 N., R. 59 E.,
north, 40.00 chs. from cor. of T. 32 N., Rs. 58 and 59
E., falls on abrupt, ledgy E. slope, where a permanent
cor. cannot be set, therefore at

56.69 Point 54 lks. S. of true point,
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. bent,