

Subdivisions T. 19 N., R. 36 E.

Chains 80.48	Intersect N. boundary of the township, N. $89^{\circ} 56' W.$, 5.14 chs. from the cor. of secs. 34 and 35, and at point of intersection Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the ground to solid rock, in a mound of stone, for the closing cor. of secs. 2 and 3, with brass cap mkd T20NR36E S 34 S3 S2 T19NR36E CC 1928
	At base of post deposit a mkd(X)porphyry stone, 7x7x5 ins. Land, rough mountainous. Soil, rocky and gravelly clay. Timber, none. Undergrowth, medium growth sage, scatter- ing buckbrush. General drainage, E. grazing, fair.
	From the cor. of secs. 3, 4, 33 and 34, on S. boundary of township N. $0^{\circ} 01' W.$, between secs. 33 and 34 Over mountainous land through timber Asc. S. slope 45 ft. to
2.90	Thence along W. slope
13.30	Spur, projects SE. Desc. NE. slope 115 ft. to 22.80
21.80	Unused road, bears E. and W.
22.80	Asc. SE. slope 115 ft. to 34.50
24.50	Short spur, projects E. Desc. NE. slope 115 ft. to 32.30
25.05	Head of dry wash, drains SE. Asc. S. slope 130 ft. to 40.00
32.30	Spur, projects S. $75^{\circ} W.$ Desc. N. slope 115 ft. to 34.80
34.80	Asc. S. to SE. slope 260 ft. to 47.50
40.00	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd