

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 2 N., R. 34 E.

Chains From the $\frac{1}{4}$ sec. cor. . . .
 S. $89^{\circ} 51'$ W., with continuous measurement
 79.46 Fall 9 lks. S. of the cor. of secs. 1, 2, 35, and 36,
 hereinafter described

The bearing of this half mile therefore is S. $89^{\circ} 59'$ W.,
 and the distance 39.89 chs.

From the cor. of secs. 1, 2, 35, and 36
 S. $89^{\circ} 51'$ W., along S. bdy. sec. 35, T. 2 N., R. 34 E.

39.57 Fall 7 lks. N. of the $\frac{1}{4}$ sec. cor., hereinafter described
 The bearing of this half mile therefore is S. $89^{\circ} 45'$ W.,
 and the distance is 39.57 chs.

From the $\frac{1}{4}$ sec. cor. . . .
 S. $89^{\circ} 51'$ W., along S. bdy. T. 2 N., R. 34 E., setting

temporary sec. and $\frac{1}{4}$ sec. cors., at regular intervals
 of 40.00 and 80.00 chs., without finding any traces
 of original cors., and at

369.11 Fall 1.61 chs. S. of the cor. of Ts. 1 and 2 N., Rs. 33
 and 34 E.

The bearing of these four and half miles therefore is
 N. $89^{\circ} 54'$ W., and the distance 369.11 chs.

True lines

The original cor. of Ts. 1 and 2 N., Rs. 34 and 35 E. is
 a scoria stone, 22x10x9 ins., loosely set in an old
 mound of earth and stone, and marked with 6 notches on
 N., E., S., and W. faces; no accessories to cor.

Alongside original cor.,
 Set an iron post, 3 ft. long, 3 ins. dia., 4 ins. in the
 ground to solid rock, over a chiseled(X) cross, in a
 mound of stone, for the cor. of Ts. 1 and 2 N., Rs. 34
 and 35 E., with brass cap mkd

