


REESTABLISHMENT OF SURVEYS EXECUTED BY HATCH, BARKER AND EATON, U. S. DEPUTY SURVEYORS IN 1877

INDEPENDENT RESURVEY EAST BOUNDARY OF T. 1 N., R. 34 E.

Chains From the cor. of Ts. 1 and 2 N., Rs. 34 and 35 E. South on a blank line

482.43 Intersect the Mt. Diablo Base Line, S. 89° 33' E., 1.88 chs. from the original standard cor. of T. 1 N., Rs. 34 and 35 E., which is a scoria stone, 24x9x6 ins., firmly set in the ground, and marked with 6 notches on N., E., and W. faces; no accessories to cor. I additionally mark same with WP, and at point of intersection

Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the standard cor. of T. 1 N., Rs. 34 and 35 E., with brass cap mkd



1930

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.

Thence


North between secs. 31 and 36

Over gently rolling land

9.30 Surface wash, drains S. 75° E.

31.60 Wash, 8 lks. wide, 1 ft. deep, drains E.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the ¼ sec. cor., with brass cap mkd



1930

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

The original ¼ sec. cor., which is a granite stone on top of ground, and marked with ¼ on W. face, bears N. 86° 47' W., 1.68 chs; I destroy all traces of original cor.