

DEPENDENT RESURVEY NORTH BOUNDARY OF T. 27 N., R. 50 E.

Chains	Abrupt ascent of E. slope 70 ft. to 5.45
4.96	The closing cor. of secs. 5 and 6, hereinafter described
5.45	Spur, projects S. 30° E.
	Gradual ascent along steep S. slope 40 ft. to
12.50	Abrupt descent of W. slope 65 ft. to
19.60	Small seep in draw, drains SE.
	Abrupt ascent of E. slope 70 ft. to
23.25	Small spur, projects S. 30° E. about 5 chs.
	Desc. 5 ft. to
23.75	Head of small seep, drains S. 30° E. about 5 chs. to
	junction with seep from NW.
	Abrupt ascent of E. slope 180 ft. to
31.35	High spur, projects SE.
	Desc. 15 ft. to
36.35	Draw, drains SE.
	Gradual ascent along steep S. slope 130 ft. to 50.05
40.00	The original $\frac{1}{4}$ sec. cor., which is an andesite stone,
	16x8x6 ins., firmly set in the ground, and marked with
	$\frac{1}{4}$ on N. face, with mound of stone N. of cor.
	Alongside original $\frac{1}{4}$ sec. cor.
	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
	ground, for the $\frac{1}{4}$ sec. cor. of secs. 31 only, with
	brass cap mkd
	$\frac{1}{4}$ S31
	1930
	Raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high, N. of cor.
44.96	Westing of 40.00 chs. from the closing cor. of secs.
	5 and 6, on steep S. slope
	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
	ground, for the $\frac{1}{4}$ sec. cor. of secs. 6 only, with
	brass cap mkd
	$\frac{1}{4}$ S6
	1930
	Raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high, S. of cor.