

DEPENDENT RESURVEY OF PORTION OF WEST BOUNDARY

Chains	North, with continuous measurement	aniso
81.07	Fall 4 blks. E. of the sec. cor., hereinafter described	aniso
except	The bearing of this half mile therefore is N. 0° 03' W.,	aniso
and	and the distance 40.34 chs.	aniso
	True lines	aniso
	The original cor. of T. 27 and 28 N., R. 49 and 50 E.,	aniso
	is a granite stone, 18x14x10 ins., firmly set in the	aniso
	ground, and marked with 6 notches on N., S., E., and	aniso
	W. faces, and T28N on W. face, and R50E on E. face; no	aniso
	accessories to cor.	aniso
	Alongside original twp. cor.	aniso
	Set an iron post, 3 ft. long, 3 ins. dia., 16 ins. in the	aniso
	ground to solid rock, in a mound of stone, for the SE.	aniso
	cor. of T. 28 N., R. 49 E., with brass cap mkd	aniso
	T28N R49E S36	aniso
	At base of post deposit a mkd (X) granite stone, 8x5x4 ins.	aniso
	Thence from the SE. cor. of T. 28 N., R. 49 E.	aniso
	N. 0° 03' E., along E. bdy. sec. 36, T. 28 N., R. 49 E.	aniso
	Over rough mountainous land through dense sagebrush,	aniso
	scattering weeds and yellow brush	aniso
3.25	Draw, drains SE.	aniso
62.40	Abrupt ascent of 115 ft. to	aniso
10.65	Spur, projects SE.	aniso
16.20	Draw, drains NE.	aniso
24.55	Gradual ascent along E. slope 50 ft. to	aniso