

DEPENDENT RESURVEY OF PORTION OF WEST BOUNDARY
T. 27 N., R. 50 E.

Chains

81.07 The original sec. cor., which is a granite stone, 16x10x8 ins., firmly set in the ground, and marked with 5 notches on N. and 1 notch on S. faces. Cor. in good state of preservation, and becomes cor. of secs. 25 and 36, T. 28 N., R. 49 E. Thence N. 0° 54' W., along E. bdy. sec. 25, T. 28 N., R. 49 E., with continuous measurement

81.97 The closing cor. of Ts. 27 and 28 N., R. 50 E. Land, rough mountainous. Soil, sand, gravel and clay, 3rd rate. Timber, none. Undergrowth, dense sagebrush, scattering weeds and yellow brush. General drainage, SE. Grazing, fair.

DEPENDENT RESURVEY OF PORTION OF SOUTH BOUNDARY
T. 28 N., R. 49 E.
REESTABLISHMENT OF SURVEYS EXECUTED BY
STEWART T. MORSE, U. S. DEPUTY SURVEYOR IN 1901

Random lines

From the SE. cor. of T. 28 N., R. 49 E.
West along S. bdy. sec. 36, T. 28 N., R. 49 E.
40.15 Intersect the $\frac{1}{4}$ sec. cor., hereinafter described
The bearing of this half mile therefore is West, and the distance 40.15 chs.

True lines

From the SE. cor. of T. 28 N., R. 49 E.
West along S. bdy. sec. 36, T. 28 N., R. 49 E.
Over rough mountainous land
General ascent of 525 ft. to 21.90

10.73 Point for closing cor. of T. 27 N., Rs. 49 and 50 E., hereinafter described

21.90 High divide ridge, bears N. 10° W. and SE.
Desc. 80 ft. to

40.15 The original $\frac{1}{4}$ sec. cor., which is a granite stone, 15x9x6 ins., firmly set in the ground, and marked with $\frac{1}{4}$ on N. face; no accessories to cor.