

SURVEY OF PORTION OF WEST BOUNDARY T. 27 N., R. 50 E.

Chains North. along E. bdy. sec. 12, T. 27 N., R. 49 E. 32.07
 Over rough mountainous land through dense black sage,
 scattering sagebrush, bitter brush and grass.
 Asc. 25 ft. to
 2.60 Spur, projects E.
 Abrupt descent of N. slope 65 ft. to
 6.55 Draw, drains SE. about 2 chs., thence NE.
 Asc. along E. slope 85 ft. to
 9.35 Spur, projects E. about 8 chs.
 Asc. 100 ft. to
 17.20 Draw, drains S. 5° E. about 8 chs., thence E.
 Abrupt ascent of S. slope 590 ft. to 36.35
 32.07 At mid-point between closing cors. of secs. 6 and 7, and
 secs. 7 and 18
 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for the $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass
 cap mkd
 $\frac{1}{4}$
 S7
 1930
 Raise a mound of stone, 5 ft. base, 3 ft. high, E. of cor.
 36.35 Rocky ridge divide, bears NE. and SW.
 Desc. gentle N. slope 60 ft. to 47.50
 40.00 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for the $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass
 cap mkd
 $\frac{1}{4}$
 S12
 1930
 Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
 47.50 Same ridge as at 36.35, bears NW. and SE.
 Desc. N. slope 260 ft. to 73.04
 72.05 Point for closing cor. of secs. 6 and 7, hereinafter
 described