

SUBDIVISIONS T. 27 N., R. 50 E.

Chains		
	1/4	✓
	S5 S4	
	1930	
	At base of post deposit a mkd(X) granite stone, 6x5x4 ins.	
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.	
45.90	Two strand barb wire fence, bears N. 62° 30' E. and S. 62° 30' W.	
46.80	Spur, projects E.	
	North gable end of S. H. Linka's house, bears S. 75° 04' E.	
	NW. gable end of barn, bears S. 67° 27' E.	
47.80	Abrupt descent of N. slope 175 ft. to	
57.20	Small draw, drains E. about 8 chs., thence SE.	
	Asc. 35 ft. to 65.90	
63.30	Small dam across draw, about 3 chs. E. of line	
64.90	Point of spur, projects E.	
	Desc. 15 ft. to 74.05	
67.50	Spring, bears E. 2.50 chs	
73.20	Irrigation ditch, 2 lks. wide, 1 ft. deep, drains SE.	
74.05	Draw, drains E. about 1 ch., thence S.	
	Asc. 15 ft. to sec. cor.	
78.45	Fence on N. side of S. H. Linka's field, bears N. 34° 04' W. and S. 34° 04' W.	
82.95	Intersect N. bdy. of twp., N. 89° 59' W., 4.58 chs. from the cor. of secs. 32 and 33, and at point of intersection	
	Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd	
	T28NR50E S 32	✓
	S5 S4	
	T27NR50E CC	
	1930	
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, S. of cor.	