

SUBDIVISIONS T. 27 N., R. 50 E.

Chains West on sectional correction line between secs. 30 and 31
 Over broken mountainous land through dense sagebrush
 from 1 to 3 ft. high, scattering black sage
 Desc. 10 ft. to
 3.50 Draw, drains SE.
 Asc. E. slope 95 ft. to
 19.25 Spur, projects SE.
 Desc. W. slope 55 ft. to
 25.70 Draw, drains SE.
 Asc. E. slope 265 ft. to 49.50
 40.00 On E. slope
 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
 ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd
 $\frac{1}{4}$ S 30
 S 31
 1930
 Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, N. of cor.
 49.50 Ridge, bears N. 10° W. and S.
 Desc. W. slope 195 ft. to
 65.45 Draw, drains S. 20° W.
 Asc. E. slope 105 ft. to
 74.75 Spur, projects S. about 10 chs.
 Desc. W. slope 50 ft. to
 78.20 Draw, drains SE. about 20 chs. to junction with draw
 Asc. 15 ft. to
 84.31 Intersect W. bdy. of the twp., South 7.99 chs. from the
 cor. of secs. 25 and 36, and at point of intersection
 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the
 ground, for the closing cor. of secs. 30 and 31, with
 brass cap mkd
 T27N
 R49E | R50E
 S30
 S36 — CC
 S31
 1930
 Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.