

SUBDIVISIONS T. 27 N., R. 50 E.

Chains

46.85 Spur, projects SE.

Desc. W. slope 40 ft. to

47.75 Draw, drains SE.

Asc. 120 ft. to

57.80 Ridge, bears N. and S.

Abrupt desc. of W. slope 80 ft. to

64.65 Draw, drains S. 10° E.

Asc. 45 ft. to

67.15 Spur, projects S. 20° E. about 12 chs.

Desc. W. slope 25 ft. to

68.25 Draw, drains SE,

Asc. E. slope 55 ft. to

72.05 Spur, projects SE.

Desc. W. slope 5 ft. to


76.25 Draw, drains SE.

Asc. 80 ft. to,

84.15 Intersect W. bdy. of twp., South 7.99 chs. from the cor.

of secs. 24 and 25, and at point of intersection, on
gentle E. slope

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the
ground, for the closing cor of secs. 19 and 30, with
brass cap mkd



Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.

Land, rough mountainous.

Soil, clay, gravel, rock and sand, 3rd rate.

Timber, none.

Undergrowth, medium bitter brush, yellow brush, scattering
sagebrush and weeds.

General drainage, S. Grazing, fair,