

SUBDIVISIONS T. 27 N., R. 50 E.

Chains	Desc. along steep N. slope 25 ft. to
84.01	Intersect W. bdy. of twp., South 7.97 chs. from the cor. of secs. 13 and 24, and at point of intersection, on steep N. slope
	Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 18 and 19, with brass cap mkd
	<div style="text-align: center;"> T27N R49E S24 S18' CC S19 1930 </div>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.
	Land, rough mountainous.
	Soil, sand, shale clay and boulders, 3rd rate.
	Timber, none.
	Undergrowth, dense black sage, scattering sage brush and bitter brush.
	General drainage, NE. Grazing, fair.
	From the cor. of secs. 17, 18, 19, and 20
	N. 0° 03' W., between secs. 17 and 18
	Over rolling mountainous land through dense black sage, scattering sagebrush
	Asc. along steep W. slope 25 ft. to
5.90	Top of ascent, bears E. and W.
	Desc. NW. slope 225 ft. to
27.15	Draw, drains NE. from junction of two draws about 1½ chs. SW.
	Asc. along gentle E. slope 15 ft. to 33.60
30.40	Old road, bears NE. and SW.
33.60	Spur, projects NE.
	Desc. 20 ft. to
37.50	Draw, drains N. 80° E.
	Asc. S. slope 65 ft. to 51.05