

SUBDIVISIONS T. 27 N., R. 50 E.

Chains

40.00

On N. slope

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$ S 7
S 18
1930

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

42.35

Spur, projects S. 70° E.

Asc. along S. slope of spur 215 ft. to

70.35

Draw, drains SE. from W. Thence along draw

71.65

Leave draw, drains E. from NW.

Asc. E. slope 55 ft. to

76.05

Desc. along N. slope 60 ft. to

81.75

Junction of two draws, drain NE. from NW. and SW.

Asc. E. slope 25 ft. to

83.90

Intersect W. bdy. of twp., South 7.91 chs. from the cor. of secs. 12 and 13, and at point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the ground to solid rock, in a mound of stone, for the closing cor. of secs. 7 and 18, with brass cap mkd

T27N
R49E R50E
S7 CC
S13
S18
1930

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land, rough mountainous.

Soil, sand, clay, and gravel, 3rd rate.

Timber, none.

Undergrowth, dense sagebrush, scattering black sage and yellow brush.

General drainage, SE. Grazing, fair.