

SUBDIVISIONS T. 27 N., R. 50 E.

Chains	Desc.
	N. slope 10 ft. to
31.15	Draw, drains S. 30° E. about 12 chs. to junction with draw.
	Asc. S. slope 70 ft. to
40.00	On spur, projecting E. Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd
	<div style="text-align: center;"> $\frac{1}{4}$ S6 S5 1930 </div>
	Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. General ascent of 180 ft. to 59.60
55.90	Begin abrupt ascent along W. slope of small rocky butte
58.65	Top of butte, bears E. 1.00 ch. distant.
59.60	Top of ascent on W. slope of butte Abrupt descent of N. slope 65 ft. to
61.95	Draw, drains S. 80° E. about 4 chs. to junction with draw
	Abrupt ascent of 380 ft. to
83.01	Intersect N. bdy. of twp., West 4.96 chs. from the cor. of secs. 31 and 32, and at point of intersection Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd
	<div style="text-align: center;"> T28NR50E S 31 S6 S5 T27NR50E CC. 1930 </div>
	Raise a mound of stone, 5 ft. base, 3 ft. high, S. of cor. Land, rough mountainous. Soil, sandy clay gravel. Timber, none. Undergrowth, dense sagebrush, black sage. General drainage, SE. Grazing, fair.