

Resurvey of portion of S. boundary T. 30 N., R. 29 E.

Chains I begin at the cor. of secs. 3, 4, 33 and 34, Ts. 29 and 30 N., R. 29 E., M. D. B. & M., which is a lava stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 3, 4, 33 and 34, Ts. 29 and 30 N., R. 29 E., with brass cap mkd

T30N R29E

S33 S34

S4 S3

T29N

1927

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Thence

West, on retracement bet. secs. 4 and 33

40.00 Old 1/4 sec. cor. bet. secs. 4 and 33, which is a basalt stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the 1/4 sec. cor. with brass cap mkd

S 33 S 4

1927

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

The bearing of this half mile is, therefore West, and the distance 40.00 chs.

Continue west on retracement with continuing measurement Wash 20lks. wide, 2 ft. deep, drains S. 15° W.

67.70

80.00

Old cor. of secs. 4, 5, 32 and 33, which is a basalt stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 4, 5, 32 and 33, with brass cap mkd