

Resurvey of portion of Subdivisions T. 30 N., R. 29 E.

Chains From the cor. of secs. 3, 4, 33 and 34, on S. bdy. of township

N. 0° 02' W., on retracement bet. secs. 33 and 34

40.00 Old 1/4 sec. cor., which is an andesite stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd

1927

No. stone available.

Dig two pits on line, north and south of cor.

The bearing of this half mile is therefore, N. 0° 02' W., and the distance 40.00 chs.

Thence

N. 0° 02' W., on retracement from 1/4 sec. cor., continuing measurement

80.00 The old cor. of secs. 27, 28, 33 and 34, which is a basalt stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 27, 28, 33 and 34, with brass cap mkd

T30N R29E

S28 | S27

S33 | S34

1927

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

The bearing of this half mile is, therefore, N. 0° 02' W. and the distance 40.00 chs.

From the cor. of secs. 27, 28, 33 and 34

N. 0° 02' W., on retracement bet. secs. 27 and 28