

Resurvey of portion of subdivisions T. 30 N., R. 29 E.

Chains

47.68

Intersect reconstructed closing corner to secs. 1 and 2
 on Sixth Standard Parallel ^{North} which is described in Book
 "B", under Group No. 112, containing the field notes
 of the survey of T. 31 N., R. 29 E., the survey of
 which was made in conjunction with the survey of this
 fractional township.

The bearing of this line is, therefore N. 0° 01' W.,
 and the distance 7.68 chs.

From the cor. of secs. 27, 28, 33 and 34

West, on retracement bet. secs. 28 and 33

40.00

Old $\frac{1}{4}$ sec. cor., which is an Andesite stone, firmly set
 in the ground, marked and witnessed as described in
 the original field notes, alongside which

Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the
 ground to solid rock, in a mound of stone, for the $\frac{1}{4}$
 sec. cor., with brass cap mkd

S. 28
 $\frac{1}{4}$
 S 33
 1927

At base of post deposit a marked (X) stone, 4x4x5 ins.

The bearing of this half mile is, therefore West, and
 the distance 40.00 chs.

From the cor. of secs. 14, 15, 22 and 23

West, on retracement bet. secs. 15 and 22

40.00

Old $\frac{1}{4}$ sec. cor., which is a Basalt stone, firmly set in
 the ground, marked and witnessed as described in the
 original field notes, alongside which

Set an iron post, 3 ft. long, 1 in. dia., 22 ins. in
 rocky ground, in a mound of stone, for the $\frac{1}{4}$ sec. cor.,
 with brass cap mkd

S 15
 $\frac{1}{4}$
 S 22
 1927