

Resurvey of portion of subdivisions T. 30 N., R. 29 E.

Chains
40.00

Old $\frac{1}{4}$ sec. cor., which is a Basalt stone, firmly set in the ground, marked and witnessed as described in the original field notes, alongside which
Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd

S 2
 $\frac{1}{4}$
S 11.
1927

No stone available.
Dig two pits on line, east and west of cor.
The bearing of this half mile is, therefore West, and the distance 40.00 chs.

Subdivisions T. 30 N., R. 29 E.

From the $\frac{1}{4}$ sec. cor. bet. secs. 10 and 11

N. 0° 02' W., bet. secs. 10 and 11

Over gently rolling land

7.40 Wash, 10 lks. wide, 1 ft. deep, drains S. 35° E.
39.98 Intersect line bet. secs. 2 and 11, and at point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 12 ins. in the ground to solid rock, in a mound of stone, for the cor. of secs. 2, 3, 10 and 11, with brass cap mkd

T30N R29E
S3 | S2
S10 | S11
1927

At base of post deposit a marked(X) stone, 4x4x6 ins.
Land, gently rolling. Soil, sandy loam.
Timber, none. Undergrowth, sage brush.
General drainage, SE. Grazing, poor

From the $\frac{1}{4}$ sec. cor. bet. secs. 2 and 11

West, bet. secs. 2 and 11

Over gently rolling land

4.10 Wash, 10 lks. wide, 1 ft. deep, drains S. 45° E
33.10 Wash, 8 lks. wide, 6 ins. deep, drains S. 40° E
40.02 The cor. of secs. 2, 3, 10 and 11