Establishment of ¼ Section Corners on W. Bdy. of T. 29 N., R. 29 E.

Chains	
40.44	Intersect the ¼ sec. cor. for secs. 13 and 18 as described in T. 29 N., R. 29 E. book "D" Group 112, made in connection with the survey of this fractional Twp. I change the markings so that this cor. will be the ¼ sec. cor. of Sec. 13 only ¼ S13 | 1927
79.90	The cor. for secs. 7 and 18, T. 29 N., R. 29 E.
	North on true line on the W. bdy. of sec. 7
0.54	The cor. for secs. 12 and 13, T. 29 N., R. 28 E.
40.27	At mid-point between cors. of secs. 7 and 18 and the cor. of secs. 1, 6, 7 and 12 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for the ¼ sec. cor. of sec. 7 only, with brass cap mkd. | ¼ S7 1927 Raise a mound of stone, 2 ft. base, 1½ ft. high E. of cor.
40.54	Intersect the ¼ sec. cor. for secs. 7 and 12, as described in T. 29 N., R. 29 E. Book "D", Group 112, made in conjunction with the survey of this fractional Twp. I change the markings so that this cor. will be the ¼ sec. cor. of sec. 12 only ¼ S12 | 1927
80.54	The cor. for secs. 1, 6, 7 and 12, as described in T. 29 N., R. 29 E., Book "D", Group 112, made in conjunction with the survey of this fractional Twp.