

RESURVEY T.19 S., R.56 E.

Chains

Unless otherwise specified all measurements are made with Lallie steel ribbon tapes 5 and 8 chs. in length compared with a Lufkin standard steel tape 1 ch. long and found correct. The measurements are made on the slope, the vertical angle determined by K. & E. improved type clinometers, and the slope measurements properly reduced to true horizontal distances.

RETRACEMENTS

Retracements of the south and east boundaries of T.19 S., R.56 E. reveal the fact that all the corners on these boundaries are missing; therefore, in order to reestablished the southeast and northeast corners of the township, I make the following retracements:

The original standard cor. of T.20 S., Rs. 56 and 57 E. on the fifth Standard Parallel South, is an oak stake, 3 ft. long, $\frac{1}{2}$ ins. square, standing in a mound of stone, marked dimly SC on N. face; other marks on stake are too weather worn to read.

From this cor., the closing cor. of T.21 S., Rs. 56 and 57 E., bears West, 2.55 chs. distant and is an oak stake, 3 ft. long, 2 ins. square, standing in a mound of earth and stone, marked T XXI S R LV11 E S VI on SE. and R LXI E S1 on SW. face; from which a juniper, 12 ins. diam., bears S.63°W., 373 lks. dist., marked TXXI S RLV11 E S1

Thence from the standard cor. of T.20 S., Rs. 56 and 57 E. North, along the E. bdy. of T.20 S., R.56 E. making careful searches at intervals of 40.00 chs. for quarter-section and section corners but none can be found, and at

480.00 Set temp. cor. of Tps. 19 and 20 S., Rs. 56 and 57 E.

Continue North with continuous measurement along the east boundary of T.19 S., R.56 E., again making