

432

RESURVEY OF THE SUBDIVISION OF T. 19 S., R. 56 E.

Chains

from which

A cattail pine, 30 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E.,
45 lks. dist., mkd. $\frac{1}{4}$ S4BT.
A cattail pine, 20 ins. diam., bears N. $40\frac{1}{4}^{\circ}$ W.,
33 lks. dist., mkd. $\frac{1}{4}$ S5BT.

Continue ascent along broken W. slope.

- 42.20 End of limestone outcroppings, bear N. 60° W. and E.
- 46.20 Divide ridge of Spring Mts., bears SE. about 10 chs. thence about S. 10° W. to a high peak, and bears N. 20° W. about 15 chs. to a high point; asc. along a steep E. slope.
- 49.30 Top of ascent on E. slope, 109 ft. above $\frac{1}{4}$ sec. cor., bears E. and W.; desc. along heavily timbered E. slope.
- 56.30 Head of a draw, 119 ft. below top of ascent, drains W. 80° E.; asc. along SE. slope.
- 61.00 Top of ascent, 94 ft. above draw, bears E. and W.; desc. along E. slope 294 ft. to 81.30 ch. point.
- 63.30 Small draw, drains E.
- 71.20 Slope changes to NE.
- 73.00 Draw, drains N. 60° E.
- 81.30 Intersect the N. bdy. of the township.

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, in a mound of stone to top of post, for the closing cor. of secs. 4 and 5, with brass cap mkd.

T18SR56E

832

S5 | S4

cc

T19SR56E

1933

from which

A limber pine, 10 ins. diam., bears S. 53° E.,
78 lks. dist., mkd. T19SR56ES4CCBT.
A limber pine, 5 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ W.,
39 lks. dist., mkd. T19SR56ES5CCBT.

Cor. stands on a NE. slope.

From the point of intersection, the cor. of secs. 32 and 33, T. 18 S., R. 56 E., heretofore described, bears S. $84^{\circ}13'$ E., 19.705 chs. dist.

the point for

From the same point, the $\frac{1}{4}$ sec. cor. of sec. 32, T18 S., R. 56 E., heretofore described, bears N. $84^{\circ}13'$ W., 22.43 chs. dist.

Land, rough mountainous.

Soil, shallow loam; 3rd rate.

Timber, yellow pine, limber pine, cattail pine and fir.

Undergrowth, mahogany brush.