

RESURVEY OF THE SUBDIVISION OF T. 19 S., R. 56 E.

Chains 80.12	The cor. of secs. 29, 30, 31, and 32. Land, rough mountainous. Soil, shallow loam; 3rd rate. Timber, cattail pine. Undergrowth, mountain shrubs.
	From the cor. of secs. 29, 30, 31, and 32. West, on a sectional correction line bet. secs. 30 and 31. Over rough mountainous land, through dense timber and scattering undergrowth; asc. along steep S. slope.
7.00	Top of ridge, bears S. 77° W. and N. 77° E., 46 ft. above cor.; desc.
20.10	Same ridge, bears N. 52° W. and S. 52° E. about 3 chs. to bend and beginning of spur projecting SW.; desc. over a W. slope.
37.50	Head of a small draw, drains S. 80° W.
40.00	On a steep SW. slope, 304 ft. below top of ridge, Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a large mound of stone to top of post, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4} \frac{S30}{S31}$ 1933
	from which
	A cattail pine, 18 ins. diam., bears N. 19½° E., 27 lks. dist., mkd. $\frac{1}{4}$ S30BT. A cattail pine, 20 ins. diam., bears S. 15° W., 27 lks. dist., mkd. $\frac{1}{4}$ S31BT.
42.40	Recross draw, drains N. 80° W.
47.80	Low rise, projects NW.; desc. over steep W. slope.
52.20	Small ravine, drains N. 60° W. about 3 chs. thence NW.; from S. 10° E.; continue along N. slope.
53.70	Low rise, projects N. about 1 ch.
54.50	Small ravine, 207 ft. below $\frac{1}{4}$ sec. cor., drains NE. to junction; asc. steep E. slope.
64.30	Spur, 114 ft. above ravine, projects N. 20° W. about 3 chs. to end in vertical ledges facing N.; desc. over steep W. slope.
68.40	Top of broken ledges, bear N. 20° W. and S. 30° W.
70.97	Intersect the W. bdy. of the township. Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a large mound of stone to top of post, for the closing cor. of secs. 30 and 31, with brass cap mkd.